

12/16/82

***** SECTION VII-SPILL OR LEAK PROCEDURES*****

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

WASTE DISPOSAL METHODS: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

*****SECTION VIII-SPECIAL PROTECTION INFORMATION*****

RESPIRATORY PROTECTION:

IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS INDICATED IN SECTION II USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. IN CONFINED AREAS USE NIOSH APPROVED AIR LINE TYPE RESPIRATORS OR HOODS.

VENTILATION: WHERE EMPLOYEES MAY BE EXPOSED, PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS IN SECTION II BELOW RECOMMENDED (ACGIH) OR REGULATED (OSHA) LIMIT. WHERE EMPLOYEES WILL NOT BE EXPOSED, KEEP LEL IN SECTION II BELOW 25% OF LIMIT

PROTECTIVE GLOVES: BUTYL RUBBER PREFERRED. NEOPRENE OR NITRILE ACCEPTABLE.

EYE PROTECTION: SPLASH PROOF GOGGLES AND/OR FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT:

PROTECTIVE CLOTHING SUCH AS BUTYL, NEOPRENE, OR NITRILE RUBBER APRON ACCEPTABLE. A SAFETY SHOWER, AN EYE BATH, AND WASHING FACILITIES SHOULD BE AVAILABLE.

***** SECTION IX-SPECIAL PRECAUTIONS*****
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

CONTAMINATED CLOTHING SHOULD BE WASHED BEFORE REUSE

DO NOT SAND, FLAME CUT, BRAZE OR WELD THE DRY COATING WITHOUT NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

OBSERVE PRECAUTIONARY LABEL WARNINGS.

PREPARED BY R. A. PROKOP

303